




Development of Inspection Tools for DST Primary Tanks & WRPS Internship Summer 2019

Patrick Uriarte (DOE Fellow)

DOE-FIU Science and Technology Workforce Development Program
Applied Research Center
Florida International University

FLORIDA INTERNATIONAL UNIVERSITY





Project Description/Background

DOE Hanford Site



- Location of underground “Tank Farms” containing nuclear waste produced from nuclear material processing for bombs during WW2 and Cold War.
- Aged Tanks, most passed their expected usage date.
- Tank Leakage of nuclear material threaten local environment and health of interstitial Columbia River of the Northwest US.





Scope/Objective

- **Double Shelled Tanks (DSTs):**
 - Primary shell sits on Refractory Pad, used to allow air cooling underneath waste holding tank.
- **Develop Inspection Tool – Mini Inspection Rover**
 - Provide visual of images of and sensor readings from undercarriage of DSTs containing 90° refractory pad air slots.
 - Overcome conditions within air slots: debris and varying weldments ridges.
 - Assist Tank & Pipeline Integrity Team of Washington River in monitoring health of the primary liners.








Method / Approach



- **Defined Project Scope**
 - Cost effective
 - Optimized size for dimension constraints of air slot
 - Overcome debris and weldment seams
 - Easily retrievable
 - Provide consistent Visual and multi-sensor data

- **Concept: Two Part Robotic System**
 - **Miniature Magnetic Adhering Miniature Rover**
 - Adheres to Primary Shell of DST, enters refractory pad air slots.
 - Contains camera, lights and other sensors (humidity, temperature, Ultra-sonic)
 - To be Train-like, multiple rovers attached each with different sensors.
 - **Controls Capsule [The Egg]**
 - Acts as “robotic brain“ contains robot computer, voltage regulators, video converters and wireless transmission capabilities.
 - Lowered and stays in annulus space while rover traverses.
 - Middle man between operator controls and rover movement/ collected sensor data.
 - Sends Mini-Rover movement commands from a distance.
 - Receives and relays sensor reading data back to the surface.






Preliminary Results/Discussion



- Mini Rover Body Design + Movement


- Uni-Body + Arm Design:

- Utilizes stabilizer arm to maintain magnetic adhesion over weldments
 - Risky potential loss of magnetic adhesion during weld climbing maneuver
 - Large Rigid Body
 - Traverse 3/8 inch weld seam





- Caterpillar Design

- Adaptable to overcome curved surfaces
 - Modular, each unit can be swapped
 - Traverse up to 1-inch weld seam
 - Increased moving part complexity



- Tank Tracks

- Help overcome debris within air slots
 - Provide better traction between Mini Rover and Primary Shell







Preliminary Results/Discussion



- Controller Capsule Design Purpose: Core of the Robotic System
 - Receives operator commands, relays commands to Mini Rover.
 - Receives Visual and sensor data, relays data to operator.
 - Acts as voltage regulator.
 - Solves voltage drop issue which occurs if the operational voltage line was directly connected to the rover over large cable length
 - Improves video signal transmission.
 - Analog camera signal converted to digital earlier, solving issue with camera feed quality. Analog camera feed suffers from voltage drop over long cable distances.
 - Onboard computer has wireless capabilities. Although not currently used, potential data transfer usage in the future.









Preliminary Results/Discussion



- Rover Electronics Board and Sensor Cap Status
 - Current electronics boards and Sensor caps are adapted for the unibody + arm rover
 - Moving forward with Caterpillar would require adapting sensor hubs and electronics boards to be spread across multiple units





- Ultrasonic Testing
 - Investigation into adapting this non-destructive, crack and thinning detecting technology
 - UT sensors require special deployment system to properly scan, therefore separate rover unit must come attached to main rover.





Conclusions

- Design and capabilities have changed over time. Finalization of design is underway.
- Push forward optimization of Rover design, sensor integration and demonstration on a full-scale mockup.







Future Work

What remains to be done?

- Tank Tracks Selection; Rigged Rubber
- Adapt ultrasonic sensor and its deployment mechanism to scan the undercarriage of the primary tank shell in DST
- Further development of reliable 90 degree turning capabilities for traversing cornered refractory pad channels.
- Preparation for deployment at Hanford Site. Construction of main power and data cables and interchangeable sensor module caps.






WRPS Internship Scope/Objective



- Tank & Pipeline Integrity Team [TAPI]
 - Investigate areas of Tank leakage and monitor overall Tank Structure Integrity
 - Double Shelled Tank Visual Inspections Reports Due by end of fiscal year
 - Assist Tank & Pipeline Integrity Team meet report deadline






WRPS Method / Approach



- Visual Inspections Reports Due end of fiscal year
- Visual Images of upper and lower tank knuckle required
- About 128 Panoramas needed complete for the report (128-256h)
- Recognized Time Constraint
 - Previous Average Time: 1~2 hour/panorama
- Reviewed reports to mimic established panorama quality standards
- Tracked Various Work Flow Methods








		Glue		7:19	7:27		
	Layer 1	Photo Organiza	22-Jul	7:35	7:37		
		Control Points		7:37	7:57		0:02
		Clean UP		7:57	7:59		0:02
		Glue		7:59	8:01		0:02
AZ-101 Riser 79	Last Layer	Photo Organiza	22-Jul	8:03	8:06		0:03
		Control Points		8:06	8:19		0:13
		Clean UP		8:19	8:20		0:01
		Glue		8:20	8:23		0:03
	Layer 1	Photo Organiza	22-Jul	8:29	8:31		0:02
		Control Points		8:31	8:43		0:12
		Clean UP		8:43	8:44		0:01
		Glue		8:44	8:50		0:06
AZ-101 Riser 81	Last Layer	Photo Organiza	22-Jul	8:52	8:54		0:02
		Control Points		8:54	9:01		0:07
		Clean UP		9:01	9:02		0:01
		Glue		9:02	9:04		0:02
	Layer 1	Photo Organiza	22-Jul	9:07	9:09		0:02
		Control Points		9:09	9:26		0:17
		Clean UP		9:26	9:28		0:02
		Glue		9:28	9:30		0:02
AZ-101 Riser 82	Last Layer	Photo Organiza	22-Jul	9:33	9:35		0:02
		Control Points		9:35	9:45		0:10
		Clean UP		10:21	10:32		0:11
		Glue		10:32	10:34		0:02
		Clean UP		10:34	10:39		0:05
	Layer 1	Photo Organiza	22-Jul				0:00
		Control Points		0:00			0:00
		Clean UP		0:00			0:00
		Glue		0:00			0:00
	Layer 1	Photo Organiza	22-Jul	10:45	10:46		0:01
AZ-101 Riser 83		Control Points		10:46	11:06		0:20
		Clean UP		11:06	11:08		0:02
		Glue		11:08	11:20		0:12
		retry		11:20	11:31		0:11
	Layer 1	Photo Organiza	22-Jul	12:48	12:51		0:03
		Control Points		12:51	13:04		0:13
		Clean UP		13:04	13:05		0:01



WRPS Conclusions



Within Annulus Space of DST:
Secondary Liner Primary Shell



- Current Panorama Times: 15-30 mins
 - Implemented automatic video frame collector.
 - Located and reduced timely sections of panorama making process.
 - Utilizing new software: AutoPano => PTGui.
- Work Document for TAPI
 - To utilize software efficiently and match new standard set.
- Support Work, Assisted Tank Monitoring Team
 - Transitioning Databases, PCSACS to OsiSoft PI
 - Backed up legacy documents and data.
 - Transferred & compiled AOI images in SST Visual Inspection Reports to dedicated digital notebook.
 - Compiled & reorganized weather and waste level data.



Acknowledgements

- **FIU ARC Mentors**
 - Dr. Dwayne McDaniel
 - Anthony Abrahao
- **WRPS Mentors**
 - Ruben Mendoza
 - Natalie Young
 - Shawn Campbell
 - Rest of TAPI Team
- **DOE-FIU Science and Technology Workforce Development Program**
- **Sponsored by the U.S. Department of Energy, Office of Environmental Management, under Cooperative Agreement #DE-EM0000598.**